Subcontracted and Hired In Plant (Minimum Requirements)


This guide sets out our minimum operational requirements for subcontracted and hired in plant on all work sites.

From 1st July 2019 all subcontracted and hired in plant must comply with the minimum requirements listed in the book below Plant that meets these minimum requirements can be approved for use by a qualified mechanic or a competent FH: manager, supervisor or site foreman. Approvals will be valid for 12 months.

Approved plant is to be 'stickered' accordingly. Inspection records shall be kept by the approving Region or Project. Stickers and checklist books are available through FH Signs & Graphics.

Suppliers trucks delivering products to site are exempt this induction process however their on site risks are to be managed via the Risk Control Plan





Windshield sticker Indicates the plant is Valid for 12 months

approved and meets the minimum requirements.



Checklist

Complete the minimum requirements checklist ... the plant must meet all the requirements to be approved for use

Park brake alarms Must incorporate an external audible alarm



CG380, CG400, CK330, CM180, Cw330, CW380, CW400, manufactured between 1993 & 2005 are not permitted on any Wellington Water sites unless these trucks have been fitted with a replacement, alternative approved, aftermarket hand brake that complies with the Heavy Vehicle Brake Rule 32015.





Swinging tail doors



Must be fully locked out when working for WW or fully complies with FH swinging tail door standard. There are many different lock options

Quick hitches

Manual pin



Fitted to all excavators 7T and above



Hitches must be 2 stage or pinned type

Pneumatic (air) hoses Must have securing straps

or double-eye, stocking type whip-socks



Certified lifting points

Paper or fixed engineers certification must be viewed

Factory fitted lifting points don't require verification





